

G72

Ambient & Chilled or Chilled & Sparkling Dispensing Tap

This two way tap is small and powerful. The simple and easy to use design fits into any environment. With the ability to dispense up to 120ltrs/h of chilled or sparkling water, it can be adapted to best suit your usage needs. Pair this Cosmetal tap with one of our undersink units to create a bespoke and preferred set up. The G72 is also compatible with a number of our drip trays.

- 30cm dispense height
- Dispenses up to 120ltrs/h of chilled and sparkling water
- manual two-way lever control
- Stainless steel dispensing tap by Cosmetal
- Small and compact for space saving

Accessories

Cosmetal Rail & Filter

High capacity Fiberdyne filter candle with reusable filter housing and installation rail. Includes all fittings and fixtures, replacement candles are also available.



Niagara IN (WG)

Recommended undersink chilling unit. dispenses 120ltrs/h of chilled and sparkling water. J-Class IN (WG) undersink chiller is also compatible.



Gas & Regulator

Carbonated coolers require a gas regulator to connect the CO² cylinder. Our REGCO2 gas regulator is suitable for 600gm disposable CO² cylinders.



Description	Code	Hourly Output Capacity	Dimensions H x W x D (mm)
G72 Tap	CETAPG72	-	345 x 100 x 90
Niagara IN (WG) Undersink Chiller	CENIN120C8WG	120ltrs/h Chilled & Sparkling	500 x 350 x 480
Niagara IN Undersink Chiller	CENIN120C8	120ltrs/h Chilled	500 x 350 x 480
J-Class IN (WG) Undersink Chiller	CEJIN45WG	45ltrs/h Chilled & Sparkling	400 x 255 x 400
J-Class IN Undersink Chiller	CEJIN45	45ltrs/h Chilled	400 x 255 x 400
H20MY IN (WG) Undersink Chiller	CEH2IN15WG	15ltrs/h Chilled & Sparkling	407 x 260 x 300
H20MY IN Undersink Chiller	CEH2IN15	15ltrs/h Chilled	407 x 260 x 235