



The ArcticChill 98 Direct Chill Cooler With Ambient Water







refreshingly different

- Chiller capacity: 30 ltr of below 12C chilled water/hour
- Ambient capacity: virtually unlimited Can be fitted with drip tray overflow kits & mains drainage
- Fits our standard cowling and wall
- FloodGuard inlet solenoid protects the cooler against large scale flooding Impressive 23cm dispensing height



ArcticChill 98 Direct Chill Cooler

Key Feature

First Select Ambient Or Cold, Then Hold The Dispensing Button Down



Accessories For The ArcticChill 98

Installation Rail With Filter. Includes Compression Fitting, 1-Micron Green Filter, Water Block, Copper Pressure Reducing Valve & Non-Retum Valve



FloodGuard - Closed Inlet Solenoid Only Opens To Allow Water Into The Cooler, When Water Is Dispensed. By Remaining Closed All Other Times It Protects The Cooler Against Leaks



Filter Housing With Carbon Block Candle & Nanofilter.



Mains Drainage -Connect The Drip Tray To Mains Drainage. Can Be Supplied With A Pump, To Pump The Water Over 50m & A Rise Of 5m.



A Pumped Main Drainage System Pumps The Waste Water From The Drip Tray Over A Distance Of 100m & A Rise Of 5m. (Factory Installed).



3 Litre Overflow Kit Connects The Drip Tray To A 3 Litre Alarmed Overflow Container. The Container Has A Tap To Empty Without Removing It.



Cowling To Fix The Cooler Securely To The Wall. (Supplied Separately)



10 Litre Overflow System With Alarm To Signal When Full. (Factory Fitted)



Description	Hourly Output			Dimensions	Weight
	Chilled	Ambient	Temp	H x W x D mm	(Kg)
POU Floor Standing	30 ltr	Indefinate	Below 12c	1135 x 340 x 340	25

Local Distributor



www.aafirst.co.uk