

WFT6 Drinking Water Fountain

Reliable High Capacity

WFT6

Durable & Reliable: High Capacity
26 Litre Per Hour Fountain



Push Button
Glass Filler
& Bubbler

Description

WFT6 Drinking Water Fountain With Push Button Operated Bubbler & Glass Filler


The WFT6 drinking water fountain has durable push button operated bubbler & glass filler faucets. It is connected to the mains water supply. Installing a carbon block filter removes the chlorine taste and smell of mains water. The water fountain needs to be connected to a waste trap, via a flexible waste pipe.

The WFT6 is not intended for outdoor use. Water fountains should only be installed by a competent & trained technician. The connection to the water mains must comply with Water regulations and the connection to the electricity supply must meet electrical requirement

Specification

- Allow 50mm clearance all round for proper Ventilation
- Mains water pressure: Min 1 bar, Max 2.5 bar (Always install a pressure reducing valve & water block)
- Turn water supply on & open bubbler & glass filler to purge all air
- Water flow control: bubbler & glass filler are adjustable
- Cabinet: Polished stainless steel
- Bracket: Wall bracket available separately
- Refrigeration system: Non toxic, non flammable with R134a refrigerant
- Cooling system & cooling capacity: Direct chill 26 litre per hour to 10°C from incoming water temperature of 20°C and a room temperature of 30°C
- Compressor & condenser: 1/6hp, cooling power 300w. Fan assisted condenser. Side vented
- Power supply: 220/240 Volt, 50 hz
- Dispensing height 210mm

Description	Dimensions H X W X D mm	Weight (Kg)
Floor Standing	1015 x 305 x 305	25.6kg



CE RoHS

AAFIRST
WATER COOLERS
& BOILERS

www.aafirst.co.uk
enquiries@aafirst.co.uk
01635 202489

refreshingly different